

**LANIER**

**SP 5200S/SP 5210SF/  
SP 5210SR**



DIGITAL IMAGING SYSTEM

*User-friendly design, productivity-enhancing results*

*Choose the Lanier SP 5200S/SP 5210SF/SP 5210SR  
for exceptional speed, multifunction versatility and  
superior productivity in an intuitive, compact design*




# More efficiency and value for everyday office tasks

Turn new challenges and everyday demands into cost-saving opportunities—with the flexible LANIER® SP 5200S/SP 5210SF/SP 5210SR Digital Imaging System. The powerful system is specifically designed to simplify everyday general office tasks for midsize workgroups. Users can quickly access exceptional multifunction performance—including monochrome copy, color scan, print and fax capabilities—to complete a wide range of projects faster with incredibly low cost-per-page. Ideal for busier workloads, it offers incredible speed, quality, finishing and intuitive controls to streamline workflow so you can manage your documents more efficiently. Its compact design is packed with versatility for optimal production and value. Plus, it's ideal for organizations deploying a print management solution with Lanier's Managed Document Services (MDS).

## ***Deliver More Efficiently***

**Complete more projects and meet even the busiest office demands in less time. The Lanier SP 5200S/SP 5210SF/SP 5210SR offers a wide range of innovative features to improve productivity.**

- Boost throughput with exceptional print speeds. The SP 5200S generates up to 47 pages-per-minute. The SP 5210SF and SP 5210SR print up to 52 pages-per-minute.
- Produce crisp, sharp text at up to 1200 x 600 dpi resolution for high-quality, compelling results.
- Take advantage of easy-to-use scanning capabilities to simplify workflow with cost-effective electronic document storage and distribution.
- Work quickly with near-instant system readiness. Warm-up time is less than 20 seconds and first print/copy times are less than 8 seconds.
- Reduce paper, mailing costs and filing space with standard automatic duplexing at nearly 90% of rated simplex speeds.
- Maximize convenience with paperless faxing. Super G3 faxing, Internet Fax, IP Fax, and LAN Fax support come standard on the SP 5210SF and are optional on the SP 5200S and SP 5210SR.



*The Lanier SP 5200S/SP 5210SF/SP 5210SR combines multifunction performance with user-friendly convenience to streamline workflow for mid-size workgroups in a wide range of environments.*



*The adjustable full-color touch screen control panel on the SP 5210SF and SP 5210SR can be tilted to give users greater visibility and easy access to the 1-bin and finisher trays. It even offers animated guidance screens for step-by-step instructions.*

### **Manage More Conveniently**

**Designed to simplify administrative and maintenance tasks, the Lanier SP 5200S/SP 5210SF/SP 5210SR includes user-friendly controls for convenient, intuitive operation.**

- Maximize uptime, streamline maintenance and reduce cost-per-page output with a high-yield, 25,000-page AIO print cartridge. When depleted, users can quickly replace the cartridge without technical assistance and recycle the spent cartridge with a provided return label.
- Gain clear, unobstructed access to critical device information from virtually any angle with an innovative 8.5" full-color tilting LCD panel.\*
- Perform all of your general office tasks from a single machine without compromising floor space or your budget. The compact footprint offers users more options for placement in more office environments.
- Access most functions, including all paper sources and the print cartridge, in even the tightest spaces via the forward-facing design.
- Set dozens of system parameters such as paper supplies and user authentication from the desktop with Web Image Monitor.
- Monitor device usage in real time with the Lanier @Remote™ Intelligent Management System and receive service notifications quickly to minimize downtime.

### **Protect Document Integrity**

**Ensure the right information gets in the right hands with advanced security features that can protect sensitive information from a multitude of threats.**

- Restrict access to system functions with user authentication. Up to 500 user codes can be registered and assigned for optimal efficiency in larger workgroups.
- Ensure optimal data protection with the Data OverwriteSecuritySystem (DOSS). When enabled, it destroys latent images and data from the internal hard drive to prevent document reconstruction.
- Stifle attempts by hackers to steal print job data and passwords transmitted over the LAN with SSL Data Encryption or Wi-Fi Protect Access Support.
- Choose the optional Enhanced Locked Print-NX to store print jobs with encrypted data at the MFP until the user swipes an ID card or enters ID information at the control panel to release the job.

### **Share Information Cost-Effectively**

**The Lanier SP 5200S/SP 5210SF/SP 5210SR offers a host of scanning capabilities to make electronic document capture and distribution quick, easy and free.**

- Speed scanning tasks with the 50-sheet Automatic Reversing Document Feeder (ARDF). It accepts originals up to 8.5" x 14" (up to 49" long in custom mode for banner scanning) for incredible flexibility and productivity.

\*SP 5210SF and SP 5210SR only.

# SP 5200S/SP 5210SF/SP 5210SR

- Convert hardcopy documents to electronic files and incorporate them into new documents using TWAIN scanning capabilities.
- Send scanned documents to hundreds of recipients cost-free over the network in one operation with Scan-to-Email/Folder/URL with LDAP support.
- Quickly transfer documents and images to portable media with Scan-to-Media (USB/SD Card) to streamline distribution in any environment.
- Reduce file sizes for scanned color documents without compromising image quality with high compression PDF for faster transmission and printing.

## Connect Your User Network

The Lanier SP 5200S/SP 5210SF/SP 5210SR includes flexible networking support that enables workgroups to produce a wide range of jobs efficiently.

- Use the robust Controller to support advanced networking features, device monitoring utilities and data protection functions, including innovative device customization and host print capabilities.
- Complete multiple projects with ease. Powerful performance from the 533 MHz processor provides the bandwidth to prepare data streams and expedite project queues to meet the needs of corporate workgroups with 8.5" x 11"/A4 monochrome workflows.
- Enjoy full compatibility throughout the office with standard USB 2.0 Hi Speed Interface and Ethernet connectivity, including support for PCL and genuine Adobe PostScript<sup>3</sup> in Windows and Macintosh network environments.
- Store up to 3,000 documents (up to 9,000 pages) on the powerful 128 GB Hard Disk Drive for easy, secure document management.


## Handle Every Task

Engineered to help users complete everyday office tasks with ease, the Lanier SP 5200S/SP 5210SF/SP 5210SR offers flexible media handling and finishing to expedite workflow.

- Support up to 8.5" x 14" paper sizes with front-loading, user-adjustable paper sources.
- Increase paper supply without compromising floor space. Up to three additional paper trays can be added for a maximum paper capacity of 2,300 sheets.
- Finish sets up to 50 pages automatically, and offset stack up to 250 sheets, with the internal finisher that comes standard on the SP 5210SR.
- Accommodate stocks up to 59 lb. Bond/120 lb. Index (220 g/m<sup>2</sup>) from any paper source to ensure print jobs are executed on time and deadlines are met.
- Enhance envelope output productivity with universal feeding.
- Extend acceptable paper sizes up to 35" long in the bypass tray to accommodate banner printing and keep more projects in house.



A USB Type A port is conveniently located in the control panel for quick and easy printing from/scanning to removable media.



These flexible systems can be configured for desk or floor placement. Stack up to 3 optional Paper Feed Units to boost input capacity to 2,300 sheets.\* The Paper Feed Unit TK1100 with casters is designed specifically for floor placement.

\*Requires the assistance of a service technician.

## The Total Green Office Solution



Lanier continues its long-standing commitment to developing office solutions with environmentally friendly and superior energy- and supply-saving features, without compromising productivity.

# SP 5200S/SP 5210SF/SP 5210SR

**User-friendly design improves office productivity.**

### User-Adjusted LCD Control Panel\*

See the easy-to-read, tilted control panel comfortably from virtually anywhere.

### Super G3 Faxing

Perform a variety of fax functions with pre-programmed speed, quick and group dial shortcuts on the SP 5210SF. A 1-Bin Tray is included to collect inbound faxes.

### 100-Sheet Bypass Tray

Extend paper sizes up to 35" long for banner production.

### Standard 550-Sheet Paper Tray

Front-facing, user-adjustable paper trays accommodate envelopes and paper sizes up to 8.5" x 14" and stock weights up to 80 lb. Bond/120 lb. Index.

### 3 x 550-Sheet Paper Trays

Add up to three additional paper trays to expand paper capacity to 2,300 sheets.

### 50-Sheet Automatic Reversing Document Feeder (ARDF)

Process originals efficiently—up to 8.5" x 14" and custom banner scanning up to 49" long—to speed the scanning process.

### Internal Finisher

Staple up to 50 pages and stack up to 250 sheets with the space-saving internal finisher on the SP 5210SR.

### Duplex Unit

Copy and print on both sides of each sheet of paper, reducing paper usage by half.

### Easy-Grip Paper Tray Handles

Open and close doors with only one hand, sitting or standing.



\*SP 5210SF and SP 5210SR only.

**Pre-configured to meet your needs.**



Model	SP 5200S	SP 5210SF	SP 5210SR
Standard Functions	Copy / Print / Scan	Copy / Print / Scan / Fax	Copy / Print / Scan / Finishing
Print Speed	47 cpm/ppm	52 cpm/ppm	
Super G3 Faxing	Optional	Standard	Optional
Color Touch Panel	Fixed Placement	Adjustable	
Internal Staple Finisher	N/A	N/A	Standard
Inner 1-Bin Tray	N/A	Standard	N/A
Output Capacity	500 sheets	600 sheets	250 sheets

LANIER

## SP 5200S/SP 5210SF/SP 5210SR

## MAIN UNIT

<b>Configuration</b>	Desktop
<b>Printing Technology</b>	Laser beam scanning & electrophotographic printing; Monocolor toner development; All-In-One Print Cartridge Technology
<b>Scanning Technology</b>	Full-Color Flatbed Scanning w/CCD Image Sensor
<b>Scan Type</b>	Sheet, book, three-dimensional objects
<b>Print Speed (LTR)</b>	SP 5200S: 47-ppm, SP 5210SF: 52-ppm, SP 5210SR: 52-ppm
<b>First Print Speed</b>	7.5 seconds or less
<b>Warm-up Time</b>	20 seconds or less
<b>Grayscale</b>	256 levels
<b>Copy Resolution</b>	600 x 600 dpi via Platen Glass, 600 x 300 dpi via ARDF
<b>Print Resolution</b>	1200 x 600 dpi, 600 x 600 dpi, 300 x 300 dpi
<b>Fax Resolution</b>	200 x 200 dpi, 200 x 100 dpi standard; 200 x 400 dpi, 400 x 400 dpi with optional memory
<b>Document Feeding</b>	Automatic Reversing Document Feeder (Standard), Original Capacity: 50 sheets Original Size: 5.5" x 8.5" - 8.5" x 14" (128 mm x 139.7 mm - 216 mm x 355.6 mm); Custom: Up to 49.6" (1260 mm) (Simplex only) Platen: 8.5" x 11.69" (216 x 297 mm) ARDF: 8.5" x 49.6" (216 x 1260 mm) Up to 999
<b>Max. Imageable Area</b>	Platen: 25% - 400% in 1% increments ARDF: 25% - 200% in 1% increments 155%, 129%
<b>Multiple Copies</b>	550-sheet Tray + 100-sheet Bypass = 650 sheets
<b>Zoom</b>	550-sheet Paper Feed Unit (Up to 3 may be installed)
<b>Presets</b>	2,300 sheets
<b>Standard Paper Supply</b>	Standard, up to 8.5" x 14" (Approx. 90% productivity)
<b>Optional Paper Supply</b>	SP 5200S: 500 sheets face down; SP 5210SF: 600 sheets face down (w/1Bin Tray); SP 5210SR: 250 sheets face down (w/Finisher)
<b>Max. Paper Capacity</b>	Standard, up to 8.5" x 14" (Approx. 90% productivity)
<b>Automatic Duplexing</b>	SP 5200S: 500 sheets face down; SP 5210SF: 600 sheets face down (w/1Bin Tray); SP 5210SR: 250 sheets face down (w/Finisher)
<b>Output Capacity</b>	Standard Tray, Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, A6, B5, B6, F/GL, Foolscap, Folio; Envelopes: Com10, Monarch, C6, C5, DL, Custom Sizes: Width: 3.86" - 8.5" (98 mm - 216 mm), Length: 5.52" - 14.01" (140 mm - 356 mm). Bypass Tray, Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, A6, B5, B6, F/GL, Foolscap, Folio; Envelopes: Com10, Monarch, C6, C5, DL, Custom Sizes: Width: 2.52" - 8.5" (64 mm - 216 mm), Length: 5.52" - 35.43" (140 mm - 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL, Foolscap, Folio; Envelopes: Com10, Monarch, C6, C5, DL, Custom Sizes: Width: 3.86" - 8.5" (98 mm - 216 mm), Length: 6.3" - 14.01" (160 mm - 356 mm)
<b>Paper Sizes</b>	Standard Tray, Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, A6, B5, B6, F/GL, Foolscap, Folio; Envelopes: Com10, Monarch, C6, C5, DL, Custom Sizes: Width: 3.86" - 8.5" (98 mm - 216 mm), Length: 5.52" - 14.01" (140 mm - 356 mm). Bypass Tray, Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, A6, B5, B6, F/GL, Foolscap, Folio; Envelopes: Com10, Monarch, C6, C5, DL, Custom Sizes: Width: 2.52" - 8.5" (64 mm - 216 mm), Length: 5.52" - 35.43" (140 mm - 900 mm). Optional PFU(s), Standard Sizes: Letter, Legal, Executive, Half Letter, A4, A5, B5, B6, F/GL, Foolscap, Folio; Envelopes: Com10, Monarch, C6, C5, DL, Custom Sizes: Width: 3.86" - 8.5" (98 mm - 216 mm), Length: 6.3" - 14.01" (160 mm - 356 mm)
<b>Paper Weights</b>	Standard & Optional Tray(s): 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m <sup>2</sup> ) Bypass Tray: 14 - 59 lb. Bond/120 lb. Index (52 - 220 g/m <sup>2</sup> ). When Duplexing: 16 - 44 lb. Bond/90 lb. Index (60 - 163 g/m <sup>2</sup> )
<b>Paper Types (all sources)</b>	Plain Paper, Recycled Paper, Middle Thick Paper, Thick Paper, Thin Paper, Transparency, Letterhead, Label, Color, Preprinted, Envelopes
<b>Dimensions (WxDxH)</b>	SP 5200S: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 5210SF: 18.1" x 20" x 27" (460 mm x 510 mm x 686 mm); SP 5210SR: 18.1" x 24.2" x 27" (460 mm x 615 mm x 686 mm)
<b>Weight</b>	SP 5200S: 99.2 lb. (45 kg); SP 5210SF: 103.6 lb. (47 kg); SP 5210SR: 116.8 lb. (53 kg) 120 - 127V, 60Hz Operating: SP 5200S: 863 W, SP 5210SF: 892 W, SP 5210SR: 858 W Energy Saver: 8 W or less
<b>Power Requirements</b>	UL60950-1, CAN/CSA C22.2 No.60950-1 (c-UL) FCC Part 15 Subpart B, IC ES-003
<b>Power Consumption</b>	ENERGY STAR Tier 2, ECP 5,500 - 15,000 total impressions/month Up to 200,000 total impressions/month
<b>Safety Regulations</b>	EMC
<b>Environmental Standard</b>	ENERGY STAR Tier 2, ECP
<b>Average Monthly Volume</b>	5,500 - 15,000 total impressions/month
<b>Maximum Duty Cycle</b>	Up to 200,000 total impressions/month

## PRINT CONTROLLER

<b>CPU</b>	533 MHz
<b>Memory</b>	1 GB RAM standard/maximum
<b>Hard Disk Drive*</b>	128 GB (standard)
*Includes HDD Encryption Unit and Overwrite (DOSS)	
<b>Interfaces</b>	Standard: 10/100Base-TX Ethernet, USB 2.0 Hi Speed Type B (for direct computer connection), Dual USB 2.0 Host Interfaces Type A (for external device connection), Front USB 2.0/SD Card Slot Interface (for Scan To/Print From portable media). Optional: Gigabit Ethernet (1000Base-T), IEEE 802.11a/g Wireless, Bluetooth
<b>Printer Languages/Drivers</b>	PCL 5e, PCL 6, XPS, Adobe PostScript <sup>3</sup> , PDF Direct Print, Genuine IPDS (optional)
<b>Fonts</b>	PCL: 45 fonts + 13 International fonts; PostScript 3: 136 fonts; IPDS: 108 fonts (optional)

www.lanier.com

Lanier, Five Dedrick Place, West Caldwell, NJ 07006  
Lanier® and the Lanier Logo are registered trademarks of Ricoh Americas Corporation. All other trademarks are the property of their respective owners. The content of this document, and the appearance, features and specifications of Lanier products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Lanier makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Lanier products and services are as set forth in the express warranty statements accompanying them.

<b>Supported Environments</b>	Windows XP, Vista, 7, Server 2003/2003R2, Server 2008/2008R2, Mac OS X v.10.2+, Novell NetWare v 6.5+, Citrix Presentation Server, UNIX/Linux
<b>Network Protocols</b>	TCP/IP (IPv4, IPv6), IPX/SPX, Bonjour
<b>Software Utilities</b>	Bundled Utilities: Web Image Monitor, Font Manager 2000. Optional Utilities: SmartDeviceMonitor for Admin Accounting Package, SmartDeviceMonitor for Client, DeskTopBinder Lite, @Remote Communication Gate S Pro
<b>Standard Security Features</b>	Administrator Authentication (5 levels), User Authentication (5 types), HDD Overwrite (DOSS) & Data Encryption, Secure Print, Encrypted Secure Print, Encrypted PDF Mode, Scan-to-Web Mail (SMTP over SSL), IP Address Filtering, Transport Layer Security (TLS), SSL Communication, IPv6, IP Sec, SNMPv3, Quota Setting IEEE802.11 a/g Interface Unit Type J; Gigabit Ethernet Board Type C; Bluetooth Interface Unit Type D; IPDS Unit Type S210; Data Overwrite Security Unit Type I*; Remote Communication Gate A; Fax Option Type SP5200; Fax Memory Unit Type B 32MB; Telephone Handset Type 1018; HotSpot MFP Option Type E; Browser Unit Type E; File Format Converter Type E
<b>Controller Options</b>	

\*For Common Criteria Certification (CCC) use. Certification pending.

## SCANNER

<b>Scanner Type</b>	Full Color CCD
<b>Scanning Resolutions</b>	Scan-To Modes: 100/200/300/400/600 dpi (Black & White, ARDF & Platen); 100/200/300 dpi (Full Color, ARDF); 100/200/300/400/600 dpi (Full Color, Platen). TWAIN/WSD/WIA: 100 - 600 dpi in 1% increments (Black & White, ARDF); 100 - 1200 dpi in 1% increments (Black & White, Platen); 100 - 600 dpi in 1% increments (Full Color, ARDF & Platen) 200 dpi Over 30-ijpm (B&W/F/C, LTR @ 200 dpi) Platen: Up to 8.5" x 11.7" (216 mm x 297 mm); ARDF: Up to 8.5" x 49.6" (216 mm x 1260 mm) Network: TCP/IP; Scan-to-Email: POP, SMTP; Scan-to-Folder: SMB, FTP, NCP
<b>Default Resolution</b>	B&W Text, B&W Text/Line Art, B&W Text/Photo, B&W Photo, Grayscale, Full-Color Text/Photo, Full-Color Glossy Photo, Auto Color Select (ACS) Auto + 7-step Manual scale
<b>Scanning Speed</b>	Supported
<b>Max. Original Size</b>	Supported
<b>Protocols</b>	Single/Multi Page TIFF, Single Page JPEG, Single/Multi Page PDF, High Compression PDF
<b>Scan Modes</b>	Scan-to-Email, Scan-to-Folder (SMB/FTP/NCP); Scan-to-URL, Scan-to-Media (USB/SD Card) Standard; Authorization: SMTP authentication, POP before SMTP authentication 500; Attention: To, cc, bcc
<b>Image Density</b>	Supported
<b>Image Rotation</b>	Supported
<b>SADF/Batch Mode</b>	Supported
<b>Supported File Formats</b>	Standard - All models + Web Services (WSD) Scanner for Vista; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2008/R2; Scan Modes: Standard, Photo, OCR, Filing; Image Adjustment: Brightness, Contrast, Threshold, Gamma Adjustment, Halftone Pattern Date, Page Number, Text
<b>Scan-To Modes</b>	
<b>Scan-to-Email</b>	
<b>Max. Addresses/Send</b>	500
<b>LDAP Search</b>	Supported
<b>Maintain E-mail Address</b>	Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin Up to 2 GB without restriction
<b>E-mail Attachments</b>	Yes
<b>Input File Name</b>	Up to 128 characters
<b>Input Subject</b>	Up to 80 characters + 5 pre-registered messages
<b>Input Body Message</b>	Standard; Protocol Support: SMB, FTP, NCP
<b>Scan-to-Folder</b>	Direct input from control panel, Web Image Monitor, SmartDeviceMonitor for Admin 100
<b>Maintain Address</b>	500
<b>Max. Folders/Send</b>	Up to 2000 MB
<b>Max. Addresses/Send</b>	500
<b>File Attachment Size</b>	Yes
<b>Input File Name</b>	Standard - All models + Web Services (WSD) Scanner for Vista; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2008/R2; Scan Modes: Standard, Photo, OCR, Filing; Image Adjustment: Brightness, Contrast, Threshold, Gamma Adjustment, Halftone Pattern Date, Page Number, Text
<b>Network TWAIN Scanning</b>	
<b>Endorse</b>	

## DOCUMENT SERVER

<b>Total HDD Capacity</b>	128 GB (Shared with other functions)
<b>Max. Stored Documents</b>	3,000 documents
<b>Max. Pages per Document</b>	2,000 pages

## FAX OPTION TYPE SP5200

(Standard for SP 5210SF, Optional for SP 5200S/ 5210SR)	
<b>Type</b>	Super G3 Transceiver
<b>Circuit</b>	PS/TN, PBX
<b>Number of Lines</b>	1
<b>Compatibility</b>	ITU-T, Group 3
<b>Resolution (dpi)</b>	200 x 100, 200 x 200, 200 x 400, 400 x 400 (for Internet & IP Fax, requires optional SAF memory)

<b>Modem Speed</b>	33,600 bps - 2,400 bps w/Auto Fallback
<b>Compression Method</b>	MH, MR, MMR, JBIG
<b>Transmission Speed</b>	G3: Approximately 2 seconds/page (w/JBIG) G3: Approximately 3 seconds/page (w/MMR) Up to 40-ppm (B&W, LTR @ 200 x 100 dpi)
<b>Scanning Speed</b>	See Scanner & Document Feeding Specifications
<b>Original Capacity/Size</b>	Up to 2,000 Quick Dial numbers in Address Book 100 Group Dial numbers (500 locations per Group) Standard: 4 MB RAM (approx. 320 pages) Maximum: 28 MB RAM (approx. 2,240 pages)
<b>Auto Dialing</b>	
<b>Page Memory Capacity</b>	1 hour
<b>Memory Backup</b>	LAN Fax, Internet Fax (T.37), IP Fax (T.38)
<b>Additional Fax Modes</b>	Standard on SP 5210SF, requires Fax Option Type 5200 for SP 5200S and SP 5210SR; Connection: 10/100Base-TX Ethernet, IEEE 802.11 a/g Wireless, or Gigabit Ethernet interface; Protocol: G3; Max. Addresses Per TX: 500; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2008/R2; Document Size: Letter, Legal, A4, A5
<b>LAN Fax</b>	Standard on SP 5210SF, requires Fax Option Type 5200 for SP 5200S and SP 5210SR; Connection: 10/100Base-TX Ethernet, IEEE 802.11 a/g Wireless, or Gigabit Ethernet interface; Protocol: G3; Max. Addresses Per TX: 500; Operating Systems: Windows XP, Server 2003, Vista, 7, Server 2008/R2; Document Size: Letter, Legal, A4, A5
<b>Internet Fax</b>	Standard on SP 5210SF, requires Fax Option Type 5200 for SP 5200S and SP 5210SR; Connection: 10/100Base-TX Ethernet, IEEE 802.11 a/g Wireless, or Gigabit Ethernet interface; Protocol: T.37 Full Mode; Max. Addresses Per TX: 500; Transmission Function: Conversion of files to TIFF format for E-mail TX to a PC; Original Size: Letter, A4
<b>IP Fax</b>	Standard on SP 5210SF, requires Fax Option Type 5200 for SP 5200S and SP 5210SR; Connection: 10/100Base-TX Ethernet, IEEE 802.11 a/g Wireless, or Gigabit Ethernet interface; Protocol: T.38, TCP, UDP/IP communication; TX/RX Function: To/from IP Fax compatible machines via network; To/from G3 Fax machines via VoIP gateway; Original Size: Letter, A4 (216 mm x 356 mm); Custom: Up to 8.5" x 47" (216 mm x 1200 mm)

## HARDWARE ACCESSORIES

<b>Optical Paper Feed Unit (TK1090)</b>	550 sheets, 1 or 2 units may be installed Capacity Paper Size Range Paper Weight Dimensions (WxDxH) Weight
<b>Optical Paper Feed Unit with Casters (TK1100)</b>	550 sheets, 1 unit may be installed as bottom PFU Capacity Paper Size Range Paper Weight Dimensions (WxDxH) Weight
<b>Internal Finisher (Standard for SP 5210SR only)</b>	250 sheets Tray Capacity Modes Paper Weight Stapling Staple Sheet Sizes Staple Capacity (21 lb. Bond, 80g/m <sup>2</sup> ) Stack Capacity after Stapling Staple Paper Weight Staple Cartridge Capacity 1-Bin Tray (Standard for SP 5210SF only) Tray Capacity Paper Weight

## SUPPLIES AND CONSUMABLES

<b>Item</b>	<b>Yield</b>
Black AIO Print Cartridge SP 5200HA	25,000 pages*
Staple Type T	5,000/carton
Refill Staple Type T	10,000/carton
Maintenance Kit SP 5200	120,000 pages

Includes 1 Fusing Unit, 1 Transfer Roller, 5 Feed Rollers and 5 Friction Pads

\*Declared yield values based on ISO/IEC 19752. Actual yields may vary based on types of images printed and other factors.

The Lanier SP 5200S/SP 5210SF/SP 5210SR ships with one starter AIO cartridge yielding 6,000 pages. All other consumables ship at full yield.

For maximum performance and yield, we recommend using genuine Lanier parts and supplies.

Specifications subject to change without notice.

## WARRANTY

The Lanier SP 5200S/SP 5210SF/SP 5210SR is under warranty against defects for a period of one year from the date of purchase. Consumables are under warranty for a period of 90 days from the date of purchase or until depleted, whichever comes first. Please refer to warranty documents shipped with the product for more details.

